

LIGCHINE

SCREEDSAVER® ELITE-D



Meet the modified SCREEDSAVER® ELITE-D, the best-selling offering in the Ligchine SCREEDSAVER line of innovative, labor-saving machines. The SCREEDSAVER ELITE-D is loaded with features including all-wheel drive, heavy-duty boom reaching 18 feet and 33-gallon on-board fluid tank.

Key Features:

The SCREEDSAVER ELITE-D includes a 10 foot high performance head, selectable all-wheel drive and revised remote control system.

Engine:

Kubota V1505, 4-cylinder, diesel engine.

Lighting System:

Front and rear LED pod lighting.

Diagnostic Display:

Readily accessible Parker touch-screen display with full diagnostics capability.

Transport:

Ease of transport with a 3/4 ton pickup truck and trailer.

LIGCHINE

SCREEDSAVER® ELITE-D



Engine Size	Kubota V1505, 4-cylinder / 3,000 rpm, diesel
Machine Size (retracted)	W-5' 9" (1.79 m) x L-14' 6" (4.45 m) x H-5' 5" (1.67 m)
Machine Weight	6,540 lbs. (Including screed head and full tank)
Steering System (hydraulic)	Front-wheel steering
Drive System (hydraulic)	4 wheel proportional
Parallel to the Pour Driving Capable	Yes – 360 degree drive frames (zero turn capable)
Lighting System	2 forward and 1 rear facing LED light pods
Machine Operation Control	100% Wireless Remote Control
Coverage per screed pass (no overlap)	216 sq. ft. (20 sq. m)
Screed Head	10' High Performance
Boom Reach	18' (5.5 m)
Self-contained Concrete Additive Sprayer System	Standard
Diagnostics (hydraulic, electrical, engine and laser)	Standard- Parker MD4, 7" touch-screen color display
Transport with Pickup Truck and Trailer	Yes
Machine Length When in Trailer Mode	23' (7.01 m)
Grade/Slope/Dual Slope control (standard)	Topcon LS-B200
Contoured Slope 3D Capable (optional)	Topcon 3D LPS Robotic