

LIGCHINE

ST60



Ligchine® is proud to unveil the ST60™, the industry's first laser-guided boom-screed attachment for skid steers. Built to make boom screed technology more accessible than ever, the ST60 pairs seamlessly with all major skid loader brands. It is also compatible with telehandlers, wheel loaders, and most machines featuring a quick-attach plate.

This attachment is ideal for smaller concrete contractors looking to step into laser-guided screeding, as well as for equipment rental companies seeking a versatile, easy-to-use, high-demand attachment.

The ST60 comes standard with LS-B200W laser receivers and is 3D-ready for contoured slopes (optional). It features a 7-1/2 foot boom reach and an 8-foot screed head that uses a roller rather than an auger. The roller design provides increased durability, extends the service life of the screed head, and allows bi-directional screeding.

*PRE-PRODUCTION MODEL SHOWN, SPECIFICATIONS SUBJECT TO CHANGE

[LIGCHINE.COM](https://www.ligchine.com)

MACHINE DETAILS & SPECS

ST60

Blending the benefits of drive-in and boom laser-guided screeds, the ST60 features a first-of-its-kind boom design that enables long, continuous concrete pulls. By extending the boom while backing up the skid steer, operators can achieve large-scale concrete screeding with ease.

The ST60 utilizes a wired Cavotec pendant for in-cab or out-of-cab control and supports one- or two-person operation to optimize leveling performance. The attachment is transportable via pickup truck and trailer and incorporates dual caster wheels to maintain accuracy and stability on the subgrade.



Machine Size (retracted)	W-5' 5" (1.7 m) x L-8' 10" (2.7 m) x H-5' 4" (1.6 m)
Machine Weight	2,800 lbs. (1270 kg)
Machine Operation Control	Wired Cavotec Pendant Style
Coverage Per Screed Pass (no overlap)	64 sq. ft. (6 m ²)
Screed Head Width	8' (2.4 m)
Boom Reach	7'6" (2.2 m)
Transport with Pickup Truck and Trailer	Yes
Grade/Slope/Dual Slope Control (standard)	Topcon® LS-B200W Receivers (included)
Contoured Slope 3D Capable (optional)	Topcon® LPS Robotic

